

## BULLETIN

### Petromin Super Diesel Turbo CF-4

#### Description

Petromin Super Diesel Turbo (CF-4) is high quality multi-grade heavy-duty diesel engine oil developed from the latest lubrication technology. They exceed meet the performance requirements of naturally aspirated, supercharged, and turbo charged high output diesel engines.

#### Benefits

- Can be used for all seasons.
- Maintains high engine cleanliness.
- Greater control of deposit formations.
- Prolonged oil life due to high oxidation stability at high temperatures.
- Excellent shear stability, maintains its viscosity grade.
- Protects against rust, wear and sludge formation.

#### Application

Petromin Super Diesel Turbo (CF-4) is suitable for use in heavy duty and high speed diesel engines and are particularly suited for heavy duty truck applications. They can also be used where API CE, CD oils are recommended.

#### Performance Level

API	CF4
MAN	271
ACEA	E2-96
VOLVO	VDS
MB	228.1
ALLISON	C4
MACK	EO-K/2

#### Product Characteristics\*

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE Grade	-	<b>20W50</b>	-
Specific Gravity @ 15 °C	-	0.894	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	167.2	ASTM D-445
@ 100 °C	mm <sup>2</sup> /s	18.4	ASTM D-445
Viscosity Index	-	123	ASTM D-2270
Flash Point, COC	°C	244	ASTM D-92
Pour Point	°C	-24	ASTM D-97
Colour	-	L 3.0	ASTM D-1500
Sulphated Ash	% wt.	1.15	ASTM D-874
Base Number	mg KOH/g	8.5	ASTM D-2896
Product Code		<b>1640</b>	

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.