

DESCRIPTION

PETROMIN DIESEL HD monograde diesel engine oil Series is designed for automotive and industrial use. Formulated from high quality base stocks and contain a balanced additive system which includes dispersants, detergents, rust inhibitors, anti-oxidant and anti-wear agents.

APPLICATION

PETROMIN DIESEL HD oil Series is recommended for automotive diesel engines in light trucks, vans, pick-ups and buses as well as in lightly loaded stationary engines.

BENEFITS

- Cleaner engines.
- Protection against mechanical wear.
- Protection against low-temperature rusting and corrosive wear.

PERFORMANCE LEVEL

API..... CF

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE			TEST METHOD	
SAE Grade	-	30	40	50	-	
Specific Gravity @ 15 °C	-	0.8935	0.8978	0.9003	ASTM D-4052	
Viscosity	@ 40 °C	mm ² /s	90.22	146.20	210.8	ASTM D-445
	@ 100 °C	mm ² /s	10.73	14.78	18.35	ASTM D-445
Viscosity Index	-	103	100	96	ASTM D-2270	
Flash Point, COC	°C	232	252	270	ASTM D-92	
Pour Point	°C	-18	-15	-15	ASTM D-97	
Sulphated Ash	% wt	0.71	0.71	0.71	ASTM D-874	
Color	-	2.0	2.5	3.0	ASTM D-1500	
Product Code	-	1930	1940	1950	-	

*The information and figures given here are typical of current production and conform to specifications, minor variations may occur.