

DESCRIPTION

PETROMIN SUPER DIESEL PLUS is high quality multigrade diesel engine oil developed for modern diesel engines, formulated from thermally stable mineral base oils, offering excellent dispersant/detergent characteristics, anti-oxidant and anti-wear properties with relatively high alkalinity reserve.

APPLICATION

PETROMIN SUPERDIESEL PLUS is recommended for use in modern highly rated diesel engines installed in construction, transport, agriculture and other heavy-duty equipment.

BENEFITS

- Reduced bore polishing.
- Excellent protection against corrosive wear caused by high-sulfur fuels.
- Extended engine life.
- Improved resistance to ring sticking, ring and cylinder liner wear, valve and combustion deposits.
- Improved fuel economy.
- Reduced oil consumption.

PERFORMANCE LEVEL

API..... CF

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD	
SAE Grade	-	15W40	-	
Specific Gravity @ 15 °C	-	0.8895	ASTM D-4052	
Viscosity	@ 40 °C	mm ² /s	114.9	ASTM D-445
	@ 100 °C	mm ² /s	15.07	ASTM D-445
Viscosity Index	-	136	ASTM D-2270	
Flash Point, COC	°C	236	ASTM D-92	
Pour Point	°C	-27	ASTM D-97	
Color	-	2.5	ASTM D-1500	
Sulphated Ash	% wt.	1.62	ASTM D-874	
Base Number	mg KOH/g	12.1	ASTM D-2896	
Product Code	-	2840	-	

*The information and figures given here are typical of current production and conform to specifications, minor variations may occur.