

**DESCRIPTION**

PETROMIN TURBODIESEL is high quality multi-grade heavy-duty diesel engine oil developed from the latest lubrication technology. They exceed meet the performance requirements of naturally aspirated, supercharged, and turbo charged high output diesel engines.

**APPLICATION**

PETROMIN TURBODIESEL is suitable for use in heavy duty and high speed diesel engines and are particularly suited for heavy duty truck applications. They can also be used where API CE, CD oils are recommended.

**BENEFITS**

- Can be used for all seasons.
- Maintains high engine cleanliness.
- Greater control of deposit formations.
- Prolonged oil life due to high oxidation stability at high temperatures.
- Excellent shear stability, maintains its viscosity grade.
- Protects against rust, wear and sludge formation.

**PERFORMANCE LEVEL**

API.....	CF4
MAN.....	271
ACEA.....	E2-96
VOLVO.....	VDS
MB.....	228.1
ALLISON.....	C4
MACK.....	EO-K/2

**PRODUCT CHARACTERISTICS\***

PROPERTIES	UNITS	VALUE	TEST METHOD	
<b>SAE Grade</b>	-	<b>15W40</b>	-	
Specific Gravity @ 15 °C	-	0.8888	ASTM D-4052	
Viscosity	@ 40 °C	mm <sup>2</sup> /s	115.6	ASTM D-445
	@ 100 °C	mm <sup>2</sup> /s	15.42	ASTM D-445
Viscosity Index	-	140	ASTM D-2270	
Flash Point, COC	°C	238	ASTM D-92	
Pour Point	°C	-27	ASTM D-97	
Color	-	L 3.5	ASTM D-1500	
Sulphated Ash	% wt.	1.323	ASTM D-874	
Base Number	mg KOH/g	9.0	ASTM D-2896	
<b>Product Code</b>	-	<b>2860</b>	-	

\*The information and figures given here are typical of current production and conform to specifications, minor variations may occur.